





# PRODUCT CONFORMITY CERTIFICATE

This is to certify that the

## SM200 Particulate Analyser with PM<sub>2.5</sub> & PM<sub>10</sub> Head

Manufactured by:

## OPSIS AB

P.O. Box 244 S-244 02 Furulund Sweden

has been assessed by Sira Certification Service and for the conditions stated on this certificate complies with:

**MCERTS Performance Standards for Continuous Ambient Air Quality Monitoring Systems, Version 10 (June 2016)** 

Certification Ranges:

Particulate matter (PM<sub>2.5</sub>) 0 to 200  $\mu$ g/m<sup>3</sup> 0 to 200  $\mu g/m^3$  $(PM_{10})$ 

674/0167 & 70130912 Project No.: Certificate No: Sira MC070109/02 Initial Certification: 21 May 2007 This Certificate issued: 22 May 2017 Renewal Date: 20 May 2022

**Emily Alexander** 

**Deputy Certification Manager** 

MCERTS is operated on behalf of the Environment Agency by





Unit 6. Hawarden Industrial Park Hawarden, Deeside, CH5 3US Tel: +44 (0)1244 670 900

The MCERTS certificate consists of this document in its entirety. For conditions of use, please consider all the information within. This certificate may only be reproduced in its entirety and without change To authenticate the validity of this certificate please visit www.csagroupuk.org/mcerts







#### **Certificate Contents**

Approved Site Application	2
Basis of Certification	
Product Certified	
Certified Performance	
Description	
General Notes	

## **Approved Site Application**

Any potential user should ensure, in consultation with the manufacturer, that the monitoring system is suitable for the intended application. For general guidance on monitoring techniques refer to the Environment Agency Monitoring Technical Guidance Notes available at <a href="https://www.mcerts.net">www.mcerts.net</a>

On the basis of these tests this certificate is valid when the instrument is used for urban air quality monitoring and similar applications. (sometimes rural as well depending on data)

#### **Basis of Certification**

This certification is based on the following Test Report(s) and on Sira's assessment and ongoing surveillance of the product and the manufacturing process:

TÜV Rheinland Report ref: 936/801013 dated 29/01/03

DEFRA Report ref: BV/AQ/AD202209/DH/2396 dated 05/06/06

TÜV Rheinland Report ref: 936/21205849/A dated 29/03/09

DEFRA Report ref: AGG04003328/BV/AQ/DH/2657 dated 28/09/10

TÜV Rheinland Report ref: 936/21205849/A dated 23/12/2011

### **Product Certified**

The SM200 measuring system consists of the following parts:

- SM200 analyser
- Pump module
- PM<sub>10</sub> / PM<sub>2.5</sub> inlet head

This certificate applies to all  $PM_{2.5}$  instruments fitted with software version 1.04.10 onwards (serial number 1236 onwards) and  $PM_{10}$  instruments fitted with software version 1.04 onwards (serial number 1001 onwards).

Certificate No: Sira MC070109/02 This Certificate issued: 22 May 2017







## **Certified Performance**

Unless otherwise stated the evaluation was carried out on the certification range 0 to 200  $\mu g/m^3$  for both PM<sub>2.5</sub> and PM<sub>10</sub> heads.

SM200 Particulate Analyser with PM<sub>2.5</sub> and PM<sub>10</sub> Heads

Test	Results	MCERTS specification
Constancy of the sampling volumetric flow PM <sub>2.5</sub> PM <sub>10</sub>	1.70% 1.59%	To remain constant within ± 3% of the rated value
	<5%	All instantaneous values to remain within ± 5% of the rated value
Tightness of the sampling system		
PM <sub>2.5</sub>	0.37%	<1% Leakage
$PM_{10}$	0.82%	<1% Leakage
Between sampler/instrument uncertainty for the standard method PM <sub>2.5</sub>	Note 1 Note 2 Note 3	
Full data set	0.52 μg/m3	<2μg/m³
>18µg/m³	0.50μg/m3	<2μg/m <sup>3</sup>
Between sampler/instrument uncertainty for the candidate method <b>PM</b> <sub>2.5</sub>		
Full data set	0.94μg/m³	<2.5μg/m³
>18μg/m³	1.22μg/m³	<2.5μg/m <sup>3</sup>
Between sampler/instrument uncertainty for the standard method <b>PM</b> <sub>10</sub>		
Full data set	1.11μg/m³	<2μg/m³
>30μg/m³	1.12μg/m <sup>3</sup>	<2μg/m³
Between sampler/instrument uncertainty for the candidate method <b>PM</b> <sub>10</sub>	1.12μg/111	\Zμg/!!!
Full data set	2.06µg/m³	<2.5μg/m <sup>3</sup>
>30µg/m³	1.59μg/m <sup>3</sup>	<2.5μg/m³

Certificate No : Sira MC070109/02 This Certificate issued : 22 May 2017







Test	Results	MCERTS specification
Expanded uncertainty calculated at 30μg/m³ PM <sub>2.5</sub>		
Cologne – Frankfurter Str.	17.46%	<25%
Cologne – Parking lot	13.21%	<25%
Furulund – Summer	16.38%	<25%
Furulund – Winter	15.81%	<25%
Expanded uncertainty calculated at 50μg/m³ <b>PM</b> <sub>10</sub>		
Teddington – Summer	22.32%	<25%
Birmingham – Summer	11.46%	<25%
Bristol – Summer	9.99%	<25%
Bristol - Winter	15.24%	<25%
East Kilbride – Summer	17.85%	<25%
East Kilbride – Winter	10.30%	<25%
Highest resulting uncertainty estimate comparison against data quality objective ( <b>PM</b> <sub>2.5</sub> at 30μg/m <sup>3</sup> - combined datasets)  All Data  >18μg/m <sup>3</sup>	13.11% 15.35% Note 1	W <sub>cm</sub> <w<sub>dqo W<sub>cm</sub><w<sub>dqo</w<sub></w<sub>
Highest resulting uncertainty estimate comparison against data quality objective ( <b>PM</b> <sub>10</sub> at 50μg/m <sup>3</sup> - combined datasets)  All Data  >30μg/m <sup>3</sup>	17.83% 14.81%	Wcm <wdqo Wcm<wdqo< td=""></wdqo<></wdqo 
Maintenance Interval PM <sub>2.5</sub> PM <sub>10</sub>	4 Weeks 4 Weeks	Two weeks (defined as filter exchange inlet cleaning frequency)

Note 1: Data for East Kilbride omitted due to concentrations at site being too low to count.

Note 2: The field tests on the OPSIS SM200  $PM_{2.5}$  resulted in between 42 and 94 paired measurements per site being obtained. Field tests on the OPSIS SM200  $PM_{10}$  resulted in between 17 and 66 paired measurements per site being obtained. The requirement is for a minimum of 40 measurement results per site.

Note 3: Test results were subjected to correction coefficients for slope, intercept or both.

Certificate No : Sira MC070109/02 This Certificate issued : 22 May 2017







## **Description**

The SM200 measures the attenuation of beta radiation through an un-sampled filter, and then takes a 24-hour sample before again measuring the beta attenuation.

The SM200 samples the particulate matter onto a 47mm filter. By use of beta attenuation of sampled and unsampled filters, the mass of the particulate matter can be measured. The sampling time is 24 hours.

#### **General Notes**

- 1. This certificate is based upon the equipment tested. The Manufacturer is responsible for ensuring that on-going production complies with the standard(s) and performance criteria defined in this Certificate. The Manufacturer is required to maintain an approved quality management system controlling the manufacture of the certified product. Both the product and the quality management system shall be subject to regular surveillance according to 'Regulations Applicable to the Holders of Sira Certificates'. The design of the product certified is defined in the Sira Design Schedule for certificate No. Sira MC070109/02
- 2. If certified product is found not to comply, Sira Certification Service should be notified immediately at the address shown on this certificate.
- 3. The Certification Marks that can be applied to the product or used in publicity material are defined in 'Regulations Applicable to the Holders of Sira Certificates'.
- 4. This document remains the property of Sira and shall be returned when requested by the company.

Certificate No : Sira MC070109/02 This Certificate issued : 22 May 2017